

## Chockfast group of products for industrial program

Product description	
<b>Chockfast Red</b>	CHOCKFAST Red is a three-component, high strength, 100% solids, epoxy grouting compound used to grout large machinery and to support soleplates in all types of foundations. CHOCKFAST Red has an extremely high compressive strength. This along with negligible shrinkage makes it ideal for installing critically aligned machinery within very close tolerances.
<b>Chockfast Red HF</b>	The next generation, 3-component, 100% solids epoxy grout. Our latest product in a long line of successful machinery grouting and chocking compounds. Chockfast Red HF offers excellent high-flow qualities for improved working and placement. Chockfast Red HF is suitable for small and large volume pours -achieving excellent cured properties for dependable, long-term service under industrial machinery & equipment.
<b>Chockfast Red SG</b>	CHOCKFAST RED SG is a three component, high strength, 100% solids epoxy grouting compound which is used to grout large machinery and to support soleplates in all types of foundation designs with clearances as little as 1" (25mm). CHOCKFAST RED SG has extremely high physical properties and negligible shrinkage, making it ideal for final positioning of critically aligned equipment within close tolerances. Compressors, extruders, turbines, pumps, motors and crane rails are just a few types of equipment supported on CHOCKFAST RED SG.
<b>ESCOWELD 7505/7530</b>	A 3-component, 100% solids, deep pour, epoxy grout; ESCOWELD® 7505/7530 offers many benefits designed to simplify equipment installation while providing excellent chemical resistance and vibration damping for pumps and other critically aligned rotating equipment. Pours from 2" to 18" (51 mm to 457 mm) are typical.
<b>CWC 604 Machine Bond</b>	A 3-component, 100% solids, deep pour, epoxy grout; CWC 604 Machine Bond® offers many of the same benefits characteristic of our other fine epoxy grouts, but where a lighter consistency material is required. Pours from 1" to 18" (51 mm to 457 mm) are typical.
<b>Chockfast Blue</b>	3-component, 100% solids, high chemical and temperature-resistant, high flow epoxy grout for new or retrofit installations in caustic environments. Chockfast® Blue can also be used as a substitute for steel soleplates or rails; normally used in a thickness range of 1" to 1 ½" (25 mm to 38 mm).
<b>Chockfast Orange</b>	2-component, low viscosity, structural epoxy "chock", or "poured shim" with variable hardener ratios options. Replaces tediously fitted steel chocks or shims. Assures intimate contact with machined or unmachined equipment bedplates. Virtually 100% effective bearing underneath supported equipment. Normally poured in thickness' of 1-1/4" to 2-1/2" (32 mm to 64 mm)
<b>Chockfast Black</b>	CHOCKFAST□ Black is a specifically formulated 100% solids, inert filled casting compound developed for use as a chocking material. It is a cost-effective method of maintaining permanent precise alignment of critical equipment. It will withstand severe environments involving high physical and thermal shock.
<b>Chockfast Gray</b>	2-component, thin pour "chock" or "poured shim"; designed to maintain proper alignment and support of machinery and equipment. Able to withstand severe industrial environments with a high degree of both physical and thermal shock resistance.
<b>ITW Quickset</b>	2-component, high-strength, fast-setting, multi-purpose epoxy with a convenient mixing ratio of 1:1. Sets within 15 minutes, with full cure in 6 hours.
<b>ITW PRC 100 Non-Shrink Grout</b>	A precision, non-shrink, cement grout that meets or exceeds all requirements of the Corps of Engineers CRD C-621 and ASTM C-1107.



**BIGA GROUP**

SPECIAL WELDING, SHIP / OFF SHORE / INDUSTRY SERVICE  
ENGINEERING, CONSULTING AND SURVEY  
www.bigagroup.com